

MATERIAL SAFETY DATA SHEET

RX-32004-A EPOXY BASE

Version Number 1.4 Page 1 of 7
Revision Date 03/13/2014 Print Date 3/14/2014

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION

8155 Cobb Center Drive, Kennesaw, GA 30152

Telephone : 1 (440) 930-1000 or 1 (866) POLYONE

Emergency telephone : CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure

number or accident).

Product name : RX-32004-A EPOXY BASE

Product code : FO00008696 Chemical Name : Mixture CAS-No. : Mixture

Product Use : Industrial Applications

2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight percent
Bisphenol A - Epichlorohydrin polymer	25068-38-6	60 - 100
Silica, amorphous, fumed, crystal-free	112945-52-5	5 - 10
Calcium carbonate	1317-65-3	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure: : Eyes, Skin contact, Inhalation, Ingestion

Acute exposure

Inhalation : Excessive inhalation of product vapors, especially during heating or

processing, may be irritating to respiratory system.

Ingestion : May be harmful if swallowed.

Eyes : Mild eye irritation

Skin : Prolonged or repeated skin contact can cause de-fatting and drying of

the skin which may result in skin irritation and dermatitis (rash).



MATERIAL SAFETY DATA SHEET

RX-32004-A EPOXY BASE

 Version Number 1.4
 Page 2 of 7

 Revision Date 03/13/2014
 Print Date 3/14/2014

Chronic exposure : Refer to Section 11 for Toxicological Information.

Medical Conditions Aggravated by Exposure: : None known.

4. FIRST AID MEASURES

Inhalation : Move to fresh air in case of accidental inhalation of vapors or fumes

from overheating or combustion. When symptoms persist or in all

cases of doubt seek medical advice.

Ingestion : Drink 1 or 2 glasses of water. Induce vomiting immediately and call

a physician. Never give anything by mouth to an unconscious

person.

Eyes : Immediately flush eye(s) with plenty of water. Seek medical

attention if necessary.

Skin : Wash off immediately with soap and plenty of water. If skin

irritation persists seek medical attention.

5. FIREFIGHTING MEASURES

Flash point : Greater than 200 °F (93 °C)

Flammable Limits

Upper explosion limit : no data available Lower explosion limit : no data available Auto-ignition temperature : no data available

Suitable extinguishing media : Carbon dioxide (CO2), Dry chemical, Water spray, Alcohol-resistant

toam.

Special Fire Fighting

Procedures

Fullface self-contained breathing apparatus (SCBA) used in positive

pressure mode should be worn to prevent inhalation of airborne

contaminants.

Unusual Fire/Explosion

Hazards

: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Wear appropriate personal protection during cleanup, such as

impervious gloves, boots and coveralls. Material can create slippery

conditions.

Environmental precautions : The product should not be allowed to enter drains, water courses or

the soil. Should not be released into the environment.

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid

binder, universal binder, sawdust). Package all material in



MATERIAL SAFETY DATA SHEET

RX-32004-A EPOXY BASE

Version Number 1.4 Page 3 of 7 Print Date 3/14/2014 Revision Date 03/13/2014

appropriate container for disposal.

7. HANDLING AND STORAGE

Handling Heat only in areas with appropriate exhaust ventilation.

Storage Keep containers dry and tightly closed to avoid moisture absorption

and contamination. Store in a cool dry place. Product is

hygroscopic. Protect from moisture. Keep drums tigthly closed to

prevent contamination.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Respiratory protection Under normal handling conditions a respirator may not be required.

Eye/Face Protection Safety glasses with side-shields

Hand protection Protective gloves

Skin and body protection Long sleeved shirts and long pants are adequate for normal handling.

> Where operations present a splash or spill potential, employees should wear chemically resistant clothing, boots, apron, gloves, and

eye/face protection.

Additional Protective

Measures

: Safety shoes

General Hygiene : Handle in accordance with good industrial hygiene and safety Considerations

practice. Wash hands before breaks and at the end of workday.

Engineering measures Heat only in areas with appropriate exhaust ventilation. Provide

appropriate exhaust ventilation at machinery.

Exposure limit(s)



MATERIAL SAFETY DATA SHEET

RX-32004-A EPOXY BASE

Version Number 1.4 Page 4 of 7
Revision Date 03/13/2014 Print Date 3/14/2014

Components	Value	Exposure time Exposure type		List:
Calcium carbonate	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average (TWA):		MX OEL
	20 mg/m3	Short Term Exposure Limit (STEL):		MX OEL
Silica, amorphous, fumed, crystal-free	0.8 mg/m3	Time Weighted Average (TWA):		Z3
	10 mg/m3	Time Weighted Average (TWA):	Inhalable particulate.	MX OEL
	3 mg/m3	Time Weighted Average (TWA):	Respirable dust.	MX OEL

9. PHYSICAL AND CHEMICAL PROPERTIES

Form : liquid Evapouration rate : negligible

Appearance : viscous Specific Gravity : >1

Colour : RED Bulk density : not applicable
Odour : mild Vapour pressure : <0.04 mm Hg @

20°C

Melting point/range : no data available Vapour density : Heavier than air. Boiling Point: : Not established pH : no data available

Water solubility : slightly soluble

10. STABILITY AND REACTIVITY

Stability : The product is stable if stored and handled as prescribed.

Hazardous Polymerization : Will not occur.

Conditions to avoid : Heating the product above 212 °F (100 °C) in the presence of air may

result in the formation of aldehydes. Product reacts exothermically

Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen

with isocyanates.

Incompatible Materials : Strong acids and strong bases

products (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

Hazardous decomposition

This product contains the following components which in their pure form have the following characteristics:

CAS-No. Chemical Name	Effect	Target Organ
-----------------------	--------	--------------



MATERIAL SAFETY DATA SHEET

RX-32004-A EPOXY BASE

Version Number 1.4 Page 5 of 7
Revision Date 03/13/2014 Print Date 3/14/2014

25068-38-6	Bisphenol A -	Irritant	Skin.
	Epichlorohydrin polymer		
		sensitizer	Skin.
112945-52-5	Silica, amorphous, fumed, crystal-free	Irritant	Eyes, Respiratory system.
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory
			system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
25068-38-6	Bisphenol A -	Oral LD50	11,400 mg/kg	rat
	Epichlorohydrin polymer	Dermal LD50	> 6,000 mg/kg	rabbit
112945-52-5	Silica, amorphous, fumed,	Oral LD50	3,160 mg/kg	rat
	crystal-free			

12. ECOLOGICAL INFORMATION

Persistence and degradability : no data available

Environmental Toxicity : no data available

Bioaccumulation Potential : Does not bioaccumulate.

Additional advice : no data available

13. DISPOSAL CONSIDERATIONS

Product : Where possible recycling is preferred to disposal or incineration. The

generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

Contaminated packaging : Recycling is preferred when possible. The generator of waste

material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal,

state/provincial and local regulations.

14. TRANSPORT INFORMATION

U.S. DOT Classification : Refer to specific regulation.

ICAO/IATA : Refer to specific regulation.

IMO/IMDG (maritime) : Refer to specific regulation.

15. REGULATORY INFORMATION



MATERIAL SAFETY DATA SHEET

RX-32004-A EPOXY BASE

 Version Number 1.4
 Page 6 of 7

 Revision Date 03/13/2014
 Print Date 3/14/2014

US Regulations:

OSHA Status : Classified as hazardous based on components.

TSCA Status : All components of this product are listed on or exempt from the

TSCA Inventory.

US. EPA CERCLA Hazardous Substances (40 CFR 302)

not applicable

California Proposition

: Not applicable

65

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Canadian Regulations:

National Pollutant Release Inventory (NPRI)

not applicable

WHMIS Classification : D2B

WHMIS Ingredient Disclosure List

CAS-No. 101-02-0

DSL : All components of this product are on the Canadian Domestic

Substances List (DSL) or are exempt.

National Inventories:

Australia AICS : Not determined

China IECS : Not determined



MATERIAL SAFETY DATA SHEET

RX-32004-A EPOXY BASE

Version Number 1.4 Page 7 of 7
Revision Date 03/13/2014 Print Date 3/14/2014

Europe EINECS : Not determined

Japan ENCS : Not determined

Korea KECI : Not determined

Philippines PICCS : Not determined

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.